



MLFB-Ordering data: **1LE1002-0CB32-2KA4**

Motor type: **1AV1073B**

Client order no.:

Item no.:

Order no.:

Consignment no.:

Offer no.:

Project:

Remarks:

U [V]	Δ/Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	NOM. EFF at ... load [%]			Power factor at ... load			I _A /I _N I _L /I _N	M _A /M _N T _l /T _N	M _k /M _N T _B /T _N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
230	Δ	50	0.37	- / -	1.88	1350	2.6	66.0	67.7	65.0	0.75	0.66	0.52	3.2	2.0	2.0	IE1
400	Y	50	0.37	- / -	1.08	1350	2.6	66.0	67.7	65.0	0.75	0.66	0.52	3.2	2.0	2.0	IE1
460	Y	60	0.43	- / -	1.03	1650	2.5	70.0	71.3	68.9	0.75	0.66	0.53	3.6	2.1	2.1	IE1
IM B14 / IM 3601		FS 71 M			IP55	CC032A	IEC/EN 60034	IEC, DIN, ISO, VDE, EN									

Mechanical data

Sound pressure level 50Hz/60Hz (load)	54 dB(A)	50 dB(A)
Moment of inertia	0.00077 kg m ²	
Bearing DE NDE	6202 2Z C3	6202 2Z C3
Bearing lifetime	40000 h	
Lubricants	Esso Unirex N3	
Regreasing device	No	
Grease nipple	- / -	
Type of bearing	Preloaded bearing DE	
Condensate drainage holes	No	
External earthing terminal		
Vibration class	A	
Insulation	155(F) to 130(B)	
Duty type	S1	
Direction of rotation	bidirectional	
Frame material	aluminum	
Data of anti condensation heating	- / -	
Coating (paint finish)	Standard paint finish C2	
Color, paint shade	RAL7030	
Motor protection	(A) without (Standard)	
Method of cooling	IC411 - self ventilated, surface cooled	

Terminal box

Terminal box position	top
Material of terminal box	Aluminium
Type of terminal box	TB1 B00
Contact screw thread	M4
Max. cross-sectional area	1.5 mm ²
Cable diameter from ... to ...	9.0 mm - 17.0 mm
Cable entry	1xM25x1,5
Cable gland	1 plug

Special design (0)

Environmental conditions

Ambient temperature	-20 °C - +40 °C
Altitude above sea level	1000 m